

Product data sheet

NADJA II (2-ARMED BEADED)

9.874.3042.06

LEIPZIGER LEUCHTEN



Recommended mounting height 4.00 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet


Light output 1



1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	78%
Lamp flux	4000 lm	Total flux	3119 lm
Luminous efficacy	35 lm/W	Total power	89 W
CCT	3400 K		
CRI	54		

Light output 2



1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	78%
Lamp flux	4000 lm	Total flux	3119 lm
Luminous efficacy	35 lm/W	Total power	89 W
CCT	3400 K		
CRI	54		

Mounting mode

Pole top mounted

Electric

System power: 178 W

Shape and measurements

Height: 20.08 in

Diameter: 20.08 in

Protection

IP: 55

Designation labels: CE, F