# Product data sheet

X-LINE SLIGHT SPOTS L-DOWN LED 6600 MICRO-PRM E / 2X 600 15° E 34 840 / L-1723MM S-1,5M TWO CIRCUIT
19.4398.442E.34


LUXIONA



IP 40 IK 04

Indoor luminaire. Assembly: surface mounted on slings. The body material is aluminum. Colour - RAL 9016 (white). Dimensions: 1723 x 34 x 68 mm. Diffuser: Micro-PRM (micro-prismatic diffuser PMMA) / optical system based on PMMA lenses. The efficiency of the optical system is 81,50%. Beam angle: (C0-C180) / (C90-C270) - 86,2° / 111° // (C0-C180) / (C90-C270) - 17,8° / 19,8°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 80000 h L80/B10. Luminaire luminous flux: 5856 / 1054 lm. Power of luminaire: 38,3 / 10,8 W. Luminaire's light efficiency: 152,9 / 97,6 lm/W. Driver: standard on/off (E) / standard on/off (E). Voltage 220..240 V, 50..60 Hz. Circuit load capacity: 7 (B10), 12 (B16), 12 (C10), 19 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

## Light output 1



3 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 12.767 W | LOR | 52% |
| Lamp flux | 2395 lm | Total flux | 3768 lm |
| Luminous efficacy | 188 lm/W | Total power | 38.3 W |
| CCT | 4000 K | | |
| CRI | 80 | | |

### Mounting mode

Pendant

### Shape and measurements

Length: 67.83 in
Width: 1.34 in
Height: 2.68 in

### Adjustability

Fixed

### Design

Color of housing: White

### Electric

System power: 38.3 W
Appliance Class: I

### Protection

IP: 40
IK: 04

### Other operating numbers

Ambient temperature range: 41...95°F