Product data sheet


TUBIS 90 1295MM PO 1X29W 125° 4500LM
7237614
PRACHT



IP 68 IK 08

Configurable Round tube luminaire TUBIS 90 1295mm PO 1x29W 125° 4500lm 4.000K, class I, with TW 3x1,5mm². LED round tube luminaire with MID power LEDs, integrated converter and 90 mm diameter. Rotates 360°, PRACHTOPAL housing (impact-resistant, acid/alkali resistant), silicone seals, variable mounting options (ceiling, wall, pendant), also suitable for outdoor areas. Item number: 7237614 GTIN: 4018098454533 Technical details/specification: Cover made of PO8; Housing made of PRACHTOPAL opalized; 220–240 V 0/50/60 Hz; Energy efficiency class C; Number of light sources / LED rows: 1; IP66, IP68 (2m), IPX9, IPX9K, IP65, IP67; Through-wiring in mm²: 3x1,5; Dimensions: LxWxH: 1295mm x 90mm x 103mm; Diameter: 90mm

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	29 W	CRI	80
Total flux	4500 lm	LOR	100%
Luminous efficacy	155 lm/W	Total power	29 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 50.98 in
Width: 3.54 in
Height: 4.06 in
Weight: 3.5 kg

Adjustability

Rotatable

Electric

System power: 29 W
Appliance Class: I

Protection

IP: 68
IK: 08

Other operating numbers

Ambient temperature range: -4...95°F