Product data sheet

PURA SPOT S MAXI
741753.003
RZB



IP 20 IK 03

Series: Pura Spot S Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Housing die-cast aluminium powder-coated, can be rotated 356° horizontally and swivelled 180° vertically, passive cooling, without reflector aluminium faceted, order reflector assembly separately, replaceable LED module, LED included in delivery, with multi-adapter for 3-phase tracks 230V, ceiling mounting. Available Colours: deep black, matt (RAL 9005) Type of Installation: Track on ceiling Dimensions: L 227, B 146, H 154 Lamp: LED Life time: 50000 h (L90/B10) Colour Temperature: 3100K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 2050lm System power: 28W Beam Angle: - Number of fittings B10A: 15 Number of fittings B16A: 25 Inrush current: 16A Unified Glare Ratio: 17,0 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3100 K
Nominal lamp power	28 W	CRI	90
Total flux	2050 lm	LOR	100%
Luminous efficacy	73 lm/W	Total power	28 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 5.75 in
Width: 8.94 in
Height: 6.06 in

Adjustability

Rotatable, Tiltable

Design

Color of housing: Black

Electric

System power: 28 W

Protection

IP: 20
IK: 03