Product data sheet


NOTOR 65 DYNAMIC DELTA DI 840 BLACK PD CLO SPOT 930
13680-555
FAGERHULT



IP 20


Installation Single installation in wire suspension. For wire suspension installation, wire brackets are required for flexible c/c; ordered separately, see accessories. Connection The luminaire is equipped with an insertion hole on the top for wiring. Design Body lacquered in white (RAL 9016 G40) or black (RAL 9005 G30). Indirect light is covered by an opal film that generates a broad beam and serves as a dust cover. End caps are included in the luminaire. Louvre Delta – micro-prism louvre shutters in acrylic (PMMA).

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	35 W	CRI	80
Total flux	4121 lm	LOR	100%
Luminous efficacy	118 lm/W	ULOR	70%
		Total power	35 W

Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	6 W	CRI	90
Total flux	385 lm	LOR	100%
Luminous efficacy	64 lm/W	Total power	6 W

Mounting mode

Pendant

Shape and measurements

Length: 54.33 in
Width: 2.56 in
Height: 3.66 in

Adjustability

Fixed

Electric

System power: 41 W

Protection

IP: 20

Design

Color of housing: Black, White