



Product data sheet

AGAT SLIM LED 2600 PLX EDD 34 840
19.4008.1223.34
LUXIONA



Indoor luminaire. Assembly: mounted in module ceilings. The body material is steel sheet. Colour - RAL 9016 (white). Luminaire dimensions: 591 x 115 x 88 mm. Weight 1,64 kg. Diffuser: PLX (PMMA opal). The efficiency of the optical system is 77,06%. Beam angle: (C0-C180) / (C90-C270) - 101,2° / 103,2°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 100000 (1) / 147000 (2) h L80/B10 (1) / L70/B50 (2). Luminaire luminous flux: 2017 lm. Power of luminaire: 14,4 W. Luminaire's light efficiency: 140,1 lm/W. Driver: DIM DALI (EDD). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 14 (B10), 24 (B16), 22 (C10), 36 (C16). Operating temperature range: 5 ÷ 30° C. Protection degree: IP20. Impact resistant: IK04. Protection against electric shock: I. The luminaire can be made in CLO (Constant Lumen Output) version.

Light output 1



2 x LED			
Nominal lamp power	7.2 W	LOR	83%
Lamp flux	1308 lm	Total flux	2183 lm
Luminous efficacy	182 lm/W	Total power	14.4 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.27 in

Width: 4.53 in

Height: 3.46 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 14.4 W

Controller: DALI

Appliance Class: I

Protection

IP: 20

IK: 04

Other operating numbers

Ambient temperature range: 41...86°F