
Product data sheet

LUCAS VII (1-ARMED BEADED) 9.857.2036.16

LEIPZIGER LEUCHTEN









High-quality mirror optics provide good glare protection and enable mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with fork-type painted special steel brackets -Available in any RAL or DB colour without surcharge - Pole: dia. 76 mm, please order separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



| 1 x High pressure sodium vapour lamp | | | | |
|--------------------------------------|---------|--|--|--|
| Nominal lamp power | 50 W | | | |
| Lamp flux | 3500 lm | | | |
| Luminous efficacy | 45 lm/W | | | |
| CCT | 2000 K | | | |
| CRI | 25 | | | |

| LOR | 80% |
|-------------|---------|
| ULOR | 4% |
| Total flux | 2799 lm |
| Total power | 62 W |
| | |



| 1 x High pressure sodium vapour lamp | | | | | | |
|--------------------------------------|---------|-------------|---------|--|--|--|
| Nominal lamp power | 70 W | LOR | 80% | | | |
| Lamp flux | 5600 lm | ULOR | 4% | | | |
| Luminous efficacy | 54 lm/W | Total flux | 4479 lm | | | |
| CCT | 2000 K | Total power | 83 W | | | |
| CRI | 25 | | | | | |

Mounting mode

Pole top mounted

Shape and measurements

Height: 23.62 in Diameter: 22.44 in Electric

System power: 62-83 W

Protection

IP: 55