
Product data sheet


CEILING AND WALL MOUNTED LUMINAIRE FLOW HE (HIGH EFFICIENCY
2007.1420 - FLOW CW1190 HELED1480-830 DIR DALI
REGENT



IP 44 IK 07

Ceiling and wall mounted luminaire Flow HE (High Efficiency), with LED, system power: 13 W, standby power 0.5 W, luminous flux of luminaire 1480 lm, colour rendering index CRI > 80, colour temperature 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L80 75'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, direct light emission support in aluminium natural-colour anodised, diffuser in polycarbonate (PC) satin blend white, SLA Technology (Spread Light Applicator), 1 integral control gear, DALI, Regent certified MINERGIE®-Modul luminaires S.A.F.E. 2019 (Re-0275), luminaire complies with the strict requirements for Minergie-certified luminaires. For for pendant mounting accessories to be ordered separately. protection class I, ingress protection IP44, glow wire test 850 °C, impact strength: IK 07, this product contains a light source of energy efficiency class B and EPREL registration number: 1249143 L = 1190 mm, B = 54 mm, H = 80 mm

Light output 1



1 x LED

Nominal lamp power	19.6 W	LOR	100%
Lamp flux	1480 lm	ULOR	26%
Luminous efficacy	76 lm/W	Total flux	1479 lm
CCT	3000 K	Total power	13 W
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 46.85 in
Width: 2.13 in
Height: 3.19 in
Weight: 2.814 kg

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 13 W
Appliance Class: I

Protection

IP: 44
IK: 07