


Product data sheet

EXCIS LED WIDE 4K CLO
18452-402
FAGERHULT



Installation Surface mounted, tube fitting, wire or adjustable ceiling bracket. Connection Four cable entries fitted with blanking grommets Ø 23 mm two in each end cap. Through-wiring 5x2,5 mm2 with snap-in terminal blocks at each end. With DALI connection - through-wiring 5+2x2.5 mm2 with snap-in terminal blocks at each end. Design Body of white enamelled aluminium (RAL 9016). The outer end caps are in polycarbonate. Louvre Optical line prism that gives glare-free light at the relevant angles. Reflector Symmetrical or asymmetrical satin matt metallised aluminium reflectors. Dimming DALI control with amplitude dimming. Miscellaneous Excis LED is certified according to VDE 0713.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	42 W	CRI	80
Total flux	6535 lm	LOR	100%
Luminous efficacy	156 lm/W	Total power	42 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 45.51 in
Width: 12.76 in
Height: 3.70 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 42 W

Protection

IP: 20