


Product data sheet

49 PENDO LED ROPE-SUPPORTED LIGHT FITTING
49 6401 LR SKI (49000 0064)
SCHUCH



LED rope-supported light fitting, PENDO, 69 W, 11480 lm, 166 lm/W, Class I, IP66, symmetrical wide beam, 4000 K, CRI $\geq$ 70, Ta -40 °C/+25 °C, L90>100000 h (@ Ta max), Power reduction with control phase (LR), Pane Safety glass clear, Closure Stainless steel V4A, Housing Die-cast aluminium, Colour grey, DB702N. LED rope-supported light fitting of the GreenLine series with outstanding sustainable product design. Consisting of powder-coated die-cast aluminium housing, two-part. Upper part with bracket, adjustable inclination, cable entry and pressure compensation system. Lower part with LED modules, highly-efficient optics, frameless safety glass pane and ECG, hinged and detachable. Isolating plug connection and strain relief in junction box between upper and lower part, hinged and toolless accessible. Zhaga LED modules with highly efficient optics, direct beam, Multi-Layer Technology. ECG with high surge protection, overload and short circuit protection. Rope mounting with stainless steel bracket, rotatable (360°) and tiltable (15°) for ropes Ø 6-12mm. Resource-saving and environmentally friendly thanks to interchangeability of components (no disposable light fitting). Length 550,00 mm, Width/Diameter 450,00 mm, Height 212,00 mm, Net weight 11,80 kg.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	69 W	CRI	70
Total flux	11480 lm	LOR	100%
Luminous efficacy	166 lm/W	ULOR	7%
		Total power	69 W

Mounting mode

Pendant, Contact rail

Shape and measurements

Length: 21.65 in

Width: 17.72 in

Height: 8.35 in

Adjustability

Fixed

Electric

System power: 69 W

Appliance Class: I

Protection

IP: 66

IK: 10

Designation labels: CE, ENEC