


Product data sheet

GUIDELED SL 13851 1-8H/D CGLINE+ (SET TO 3 H OPERATION)
40071353280
EATON EMERGENCY LIGHTING



• LED self-contained safety luminaire with automatic test for reduced inspection effort • Universal use for maintained and non-maintained operation and for 1 h, 3 h or 8 h operation • For autonomous installation or connection to the CGLine+ monitoring system • Environmentally-friendly due to modern lithium ion technology • Low operating costs via low connected load • Minimum maintenance effort via high LED service life (50,000 hours) • Special asymmetric optics for illumination of 5 lx vertically for first aid stations, fire fighting equipment and safety equipment acc. to EN 1838 • Simple fault analysis and status display via bicolor LED and testing button • 1 minute switch-back delay after mains return • Blocking function prevents unintended discharge during idle operating times (only with CGLine+ WEB-Controller)

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	6500 K
Nominal lamp power	6.7 W	CRI	70
Total flux	155 lm	LOR	100%
Luminous efficacy	23 lm/W	Total power	6.7 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.94 in
Width: 3.94 in
Height: 1.65 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 6.7 W
Suitable for feed-through wiring
Appliance Class: I

Information regarding emergency functions

Emergency lighting only
Emergency power supply: Single battery 1 h, Single battery 3 h, Single battery 8 h
Emergency sign: N/A

Protection

IP: 41
IK: 03