Product data sheet


LINA45-S 145S-2C0K-20GHM3/830, B
145S-2C0K-20GHM3/830
HALLA



IP 20


145S-2C0K-20GHM3/830, B Luminaire surface/suspended Material of luminaire: Colour of luminaire: Shape of luminaire: Linear Size: 1122 x 47 x 69 mm Type of installation: Surface, Suspended Distribution: Direct Optics type: Opal diffuser Protection class: I Voltage: 220-240V

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	3000 K
Nominal lamp power	1.5 W	CRI	80
Total flux	280 lm	LOR	100%
Luminous efficacy	187 lm/W	Total power	1.5 W

Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	24.9 W	CRI	80
Total flux	3730 lm	LOR	100%
Luminous efficacy	150 lm/W	Total power	24.9 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 1.85 in
Width: 44.17 in
Height: 2.72 in

Adjustability

Fixed

Electric

System power: 26.4 W
Appliance Class: I

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 20