
Product data sheet

NIX 6700 120° EM 21 IP65 840 / L-1200 MM 11.0030.2404.21

LUXIONA








Nix is a range of waterproof LED shades with multiple installation possibilities, to be placed on walls and ceilings or suspended. These luminaires are specifically indicated to ligh up premises where a high environmental protection is necessary: high levels of humidity, pollution and impact risks. Assembly: surface mounted on ceiling. The body material is polycarbonate. Colour - RAL 9006 (grey, metallic, fine structure). Luminaire dimensions: 99 x 1200 x 70 mm. Weight 2,647 kg. Diffuser: opalescent polycarbonate. Beam angle: 120°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 50000 h L70/B10. Luminaire luminous flux: 5895 lm. Power of luminaire: 52 W. Luminaire's light efficiency: 113,4 lm/W. Driver: on-off driver + emergency kit. Voltage 220..240 V, 50..60 Hz. Power factor cosp: >0,9. Operating temperature range: -20 ÷ 35° C. Protection degree: IP65. Protection against electric shock: I.

Light output 1



1	х	LED

Nominal lamp power	52 W
Lamp flux	5895 lm
Luminous efficacy	113 lm/W
CCT	4000 K
CRI	80

LOR 83%
Total flux 4920 lm
Total power 52 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 3.90 in Width: 47.24 in Height: 2.76 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 52 W Appliance Class: I

Protection

IP: 65

Other operating numbers

Ambient temperature range: -4...95°F