




Product data sheet

601 DISANLENS 4000K CRI 80 18W CLD-E WHITE
115594-07
DISANO



Housing: in extruded aluminium with end caps. Diffuser: in polycarbonate, shatterproof and V2 self-extinguishing, UV stabilised. Externally smooth and anti-dust, internally multi-grooved to increase light diffusion. Coating: polyester powder coated, UV-stabilised, anti-yellowing, phosphate pre-treatment. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. They have a degree of protection according to the EN60529 standard. Equipment: in silicone rubber; external stainless steel screws.

Light output 1 (emergency)



1 x LED			
Nominal lamp power	18 W	LOR	100%
Lamp flux	1947 lm	Total flux	1947 lm
Luminous efficacy	108 lm/W	Total power	18 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 20.47 in
Width: 5.24 in
Height: 3.43 in

Adjustability

Fixed

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 18 W
Appliance Class: I

Information regarding emergency functions

Emergency lighting only
Emergency sign: N/A

Protection

IP: 44
IK: 06
Designation labels: CE