Product data sheet


INDUSTRIAL AND WAREHOUSE LIGHTING
V1-I0-70604-04D05-6517550 OLYMP 2.0 175/200 W 175W 5000K DALI LAMBERT
VARTON



IP 65

Medium-power Industrial luminaire with wide range of wattage and optics. Housing: heatsink made of extruded aluminum, assembly and mounting elements made of steel. Secondary optics - PMMA/PC. Installation: Surface-mounted using an adjustable bracket. Angle of rotation: 0° to 180°, step of 7,5°. The luminaire has a wire for connecting to the mains. Wire length 0.3 meters. Application: Outdoor areas. Industrial facilities. Warehouses. Power factor: 0,95 Input voltage (AC, 50Hz), V: 100...305 AC frequency, Hz: 50 Input voltage (DC), V: 127...300 Flicker, %: 5 Climatic modification and category of placement: УХЛ1 Protection class: I Ingress protection (IP): IP65 Impact resistance: IK10 https://www.varton.ru/products/promyshlennoe-i-skladskoe-osveshchenie/olymp-2-0/olymp-2-0-175-200-vt/svetodiodnyy-svetilnik-varton-promyshlennyy-olymp-2-0-175-vt-5000-k-klass-zashchity-ip65-linza-120-g/

Light output 1



1 x LED

Nominal lamp power	175 W	LOR	100%
Lamp flux	26500 lm	Total flux	26502 lm
Luminous efficacy	151 lm/W	Total power	175 W
CCT	5000 K		
CRI	70		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 14.57 in
Width: 14.17 in
Height: 6.50 in

Adjustability

Fixed

Electric

System power: 175 W

Protection

IP: 65