


Product data sheet

MINI ARGOS 1 - WALL DOWNLIGHT
5401-9-7-690-XX
UNILAMP



Robust and rectangular in appearance offer multi directions of light. ARGOS can illuminate both top and bottom at the same time or single vertical direction of either top or bottom. This is a wall light with simple geometric shape, which suitable for facade application thereof. ARGOS via precise manufactured achieve reliable IP65. LED is by way of Citizen and OSRAM with brilliant color rendering. As a result improves lumen efficiency output while maintaining conservation of energy economically. SPEC • Designed, Manufactured and Tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium housing. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Safety glass cover. • Post-cured silicone gasket. • High quality LED module and driver. • Optical glass lens. • GFR PA6.6 terminal block. • Weather proof grommet. • Installation work has to be carried on according to the enclosed product manual.

Light output 1



1 x LED			
Nominal lamp power	5.2 W	LOR	100%
Lamp flux	750 lm	ULOR	7%
Luminous efficacy	144 lm/W	Total flux	750 lm
CCT	3000 K	Total power	5.2 W
CRI	80		

Mounting mode

Wall mounted

Shape and measurements

Length: 8.86 in
Width: 4.19 in
Height: 3.54 in

Adjustability

Fixed

Electric

System power: 5.2 W
Appliance Class: I

Protection

IP: 65