Product data sheet

SINUS CURVED SEGMENT DI BLACK SAT. 90° R730
P33-A39-9005E1830L1S
PLANLICHT



IP 40

low output LED 3000K CRI 90 16,4W 1718lm https://katalog.planlicht.com/en-gb/search?q=sinus%20segment

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	4.1 W	CRI	90
Total flux	430 lm	LOR	100%
Luminous efficacy	105 lm/W	Total power	4.1 W

Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	4.1 W	CRI	90
Total flux	430 lm	LOR	100%
Luminous efficacy	105 lm/W	Total power	4.1 W

Light output 3 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	4.1 W	CRI	90
Total flux	430 lm	LOR	100%
Luminous efficacy	105 lm/W	Total power	4.1 W

Light output 4 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	4.1 W	CRI	90
Total flux	430 lm	LOR	100%
Luminous efficacy	105 lm/W	Total power	4.1 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 30.12 in
Width: 30.12 in
Height: 3.94 in

Adjustability

Fixed

Electric

System power: 16.4 W

Protection

IP: 40