

Product data sheet

HERO 4 LED WIDE HTG 4K
31501
FAGERHULT




IP
66

IK
10

Installation Flush-mounted, surface-mounted tandem bracket, tube bracket, wire bracket, adjustable ceiling/wall bracket and recess frame. Installation accessories are ordered separately, see accessories. Connection 2 m connection cable (H07RN-F) with free ends. 3G1.5 mm² or 5G1.5 mm² with DALI/CLO. Design Luminaire body made of cast (RAL 9005) aluminium. Louvre frame made of coated sheet steel. Pressure balancing valve in side of luminaire body. Louvre Tempered protective glass or PMMA for higher IK classification. Reflector Symmetrical reflectors made of semi-gloss metallised aluminium. Dimming DALI control with CLO (Constant Light Output) means that the luminaire provides the same amount of light for the duration of its service life. Miscellaneous Hero is certified in accordance with VDE 0710-13. Ambient temperature -30°C/40°C. Versions with higher Ta° on request. Corrosion protection class C4/15 years.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	83 W	CRI	80
Total flux	12068 lm	LOR	100%
Luminous efficacy	145 lm/W	Total power	83 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 19.61 in
Width: 12.09 in
Height: 3.47 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 83 W

Protection

IP: 66
IK: 10