Product data sheet


SLOIN T SL LED2200-840 L1298 PC
42183682
ZUMTOBEL



IP 20 IK 07

LED light line with DALI-controllable LED converter, with cover to 50m from one piece; LED service life lasts 50000 h before luminous flux is reduced to 90% of the initial value. Chromaticity tolerance (initial MacAdam): 3. Luminaire luminous flux: 2140 lm, Luminaire efficacy: 84 lm/W. Colour rendering Ra > 80, colour temperature 4000 K. Luminaire of aluminium, white powder coated. Luminaire with completely uniform appearance due to polycarbonate cover. Luminaire consists of housing and continuous optic of polycarbonate. For installing in module ceilings with 12 mm edges and for installing in plasterboard ceilings. Armstrong® TECH ZONE compatible with ceiling types with width 100 mm. Includes gear tray, wiring, and end-cap set. Luminaire wired with halogen-free leads and covers are due to norm classified as TP(a). Degree of protection: IP40 below (IP20 above). Dimensions: 1298 x 100 x 134 mm weight: 4.4 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	25.6 W	CRI	80
Total flux	2140 lm	LOR	100%
Luminous efficacy	84 lm/W	Total power	25.6 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 51.10 in
Width: 3.94 in
Height: 5.28 in
Weight: 4.4 kg

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 25.6 W
Voltage: 220-240 V AC
Controller: DALI
Appliance Class: I

Protection

IP: 20
IK: 07
Designation labels: CE, ENEC