Product data sheet


DEFINE LED SUSPENDED LUMINAIRE S122DIP-S865D530U835-4F0-1E-UDD-A1 COOPER LIGHTING



() COOPER Ligning Solution

Surface mount slot family in 2", 3", 4" and 5" housing sizes, Specifiable to the nearest 1', Multiple lensing options: flush satin, drop, regressed and asymmetric, Multiple lumen packages, 0-10V dimming standard; DALI dimming available, 2700K, 3000K, 3500K, 4000K and 5000K correlated color temperatures, VividTune CCT tuning options from 3000K–5000K or 2700K-6500K, Integral Wavelinx, Lumawatt Pro and stand-alone sensors available, Customizable in-wall, in-ceiling and wall-to-ceiling corners available, DLC listed configurations available

Light output 1 (integrated)



LED	CCT	3500 K
48.8 W	CRI	80
5701 lm	LOR	100%
117 lm/W	ULOR	33%
	Total power	48.8 W
	48.8 W 5701 lm	48.8 W CRI 5701 lm LOR 117 lm/W ULOR

Mounting m	ode
------------	-----

Pendant

Shape and measurements

Length: 48.00 in Width: 2.00 in Height: 0.39 in

Adjustability

Fixed

Electric

System power: 48.8 W

Protection

IP: 47