Product data sheet


RIO B - DIP SWITCH - UNIVERSAL ADAPTER 3000K CRI 90 39W CLD SILVER
22106170-00
DISANO



IP 40 IK 07

Housing: in die-cast aluminium. Optics: in high-performance polished aluminium, anti-glare. Coating: epoxy polyester powder coating resistant to UV rays. Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529. Equipment: universal adapter. Warnings: DALI dimmer version -1241 and -6841 to be used with OMNITRACK PLUS. On request: - versione con sistema CASAMBI (MAX 40W). - versione with CLD-D-D (DALI).

Light output 1



1 x LED

Nominal lamp power	39 W	LOR	100%
Lamp flux	4223 lm	Total flux	4223 lm
Luminous efficacy	108 lm/W	Total power	39 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 5.75 in
Width: 5.75 in
Height: 6.46 in

Adjustability

Fixed

Design

Material impression: Aluminum
Color of housing: Silver gray

Electric

System power: 39 W
Appliance Class: II

Protection

IP: 40
IK: 07
Designation labels: CE