

Product data sheet


OKHOLM TUBE STORRUMSPENDEL T5 3X28/54W DALI
113704
DEFA LIGHTING



IP
20


Storrumsspendel i Opal acrylrør. Finnes for 3x14/24-21/39-28/54-35/49 Lengder på 625/925/1225 og 1449mm. Ø=200mm Med og uten DALI dim. Andre utførelser på forespørsel

Light output 1




3 x Fluorescent lamp tubular T5

Nominal lamp power	54 W	Socket	G5
Lamp flux	4450 lm	LOR	82%
Luminous efficacy	62 lm/W	ULOR	40%
CCT	4000 K	Total flux	10931 lm
CRI	85	Total power	177 W




3 x Fluorescent lamp tubular T5

Nominal lamp power	54 W	Socket	G5
Lamp flux	4450 lm	LOR	82%
Luminous efficacy	62 lm/W	ULOR	40%
CCT	3000 K	Total flux	10931 lm
CRI	85	Total power	177 W



3 x Fluorescent lamp tubular T5

Nominal lamp power	28 W	Socket	G5
Lamp flux	2600 lm	LOR	82%
Luminous efficacy	36 lm/W	ULOR	40%
CCT	4000 K	Total flux	6387 lm
CRI	85	Total power	177 W



3 x Fluorescent lamp tubular T5

Nominal lamp power	28 W	Socket	G5
Lamp flux	2600 lm	LOR	82%
Luminous efficacy	36 lm/W	ULOR	40%
CCT	3000 K	Total flux	6387 lm
CRI	85	Total power	177 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Height: 48.23 in
Diameter: 7.87 in

Adjustability

Fixed

Electric

System power: 177 W

Protection

IP: 20