


# Product data sheet

FLAT POLYMERO KREIS SLIM  
312087.002.2  
RZB



IP  
40

IK  
10

Series: Flat Polymero Kreis Slim Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Base: metal, powder-coated. Diffuser fastening: push lock. Diffuser: plastic (polycarbonate), opal. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 515, H 70 Lamp: LED Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK10 (20 Joule) Luminaire flux LED: 3400lm System power: 33W Beam Angle: 123° Number of fittings B10A: 53 Number of fittings B16A: 85 Number of fittings C10A: 53 Number of fittings C16A: 85 Inrush current: 0,2A Unified Glare Ratio: 20,6 EEC: A+

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 3000 K |
| Nominal lamp power | 33 W     | CRI         | 80     |
| Total flux         | 3400 lm  | LOR         | 100%   |
| Luminous efficacy  | 103 lm/W | ULOR        | 13%    |
|                    |          | Total power | 33 W   |

## Mounting mode

Wall mounted

## Electric

System power: 33 W

## Shape and measurements

Height: 2.76 in  
Diameter: 20.28 in

## Protection

IP: 40  
IK: 10

## Adjustability

Fixed