
Product data sheet


X-LINE SLIGHT SURFACE LOW UGR LED 1800 LOUVER EDD 34 840 LINE-1S / L-1196MM
19.4423.A323.34
LUXIONA



IP 40 IK 04

Indoor luminaire. Assembly: surface mounted on ceiling. The body material is aluminum. Colour - RAL 9016 (white). Dimensions: 1196 x 34 x 68 mm. Diffuser: LOUVER (anti-glare louver). The efficiency of the optical system is 71,66%. Beam angle: (C0-C180) / (C90-C270) - 46° / 44,6°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 145000 h L90/B10. Luminaire luminous flux: 1336,8 lm. Power of luminaire: 11,3 W. Luminaire's light efficiency: 118,3 lm/W. Driver: DIM DALI (EDD). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 20 (B10), 31 (B16), 33 (C10), 53 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



1 x LED

Nominal lamp power	11.3 W	LOR	52%
Lamp flux	1864 lm	Total flux	977 lm
Luminous efficacy	165 lm/W	Total power	11.3 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 47.09 in
Width: 1.34 in
Height: 2.68 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 11.3 W
Controller: DALI
Appliance Class: I

Protection

IP: 40
IK: 04

Other operating numbers

Ambient temperature range: 41...95°F