
# Product data sheet


GRANVIA PRO 3500 NARROW EDD 34 830 / L-900MM
19.4378.5H13.34
LUXIONA



IP 20 IK 06

Indoor luminaire. Assembly: directly mounted to ceiling construction or surface mounted on slings. The body material is steel sheet. Colour - RAL 9016 (white). Dimensions: 900 x 72 x 66 mm. Diffuser: optical system based on PMMA lenses. The efficiency of the optical system is 96,63%. Beam angle: (C0-C180) / (C90-C270) - 21,8° / 23,6°. Light source type: LED. Colour of the light 3000 K. SDCM=3. CRI>80. Lifetime of LED sources: 100000 h L80/B10. Luminaire luminous flux: 3466,7 lm. Power of luminaire: 19 W. Luminaire's light efficiency: 182,5 lm/W. Driver: DIM DALI (EDD). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 17 (B10), 28 (B16), 26 (C10), 41 (C16). Operating temperature range: -20 ÷ 35° C. Protection degree: IP20. Impact resistant: IK06. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

## Light output 1



3 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 6.333 W | LOR | 52% |
| Lamp flux | 1195 lm | Total flux | 1880 lm |
| Luminous efficacy | 189 lm/W | Total power | 19 W |
| CCT | 3000 K | | |
| CRI | 80 | | |

### Mounting mode

Ceiling mounted

### Shape and measurements

Length: 35.43 in
Width: 2.83 in
Height: 2.60 in

### Adjustability

Fixed

### Design

Color of housing: White

### Electric

System power: 19 W
Controller: DALI
Appliance Class: I

### Protection

IP: 20
IK: 06

### Other operating numbers

Ambient temperature range: -4...95°F