

Product data sheet


E04 WALL WHITE
E04050
LUCEPLAN



IP
20


Apparecchi a parete per interni ed esterni. Il corpo cilindrico in differenti lunghezze, si raccorda alla superficie di montaggio in maniera fluida, in un rapporto di continuità con l'architettura. Differenti ottiche e gradi di protezione (fino ad IP55) permettono di realizzare diverse soluzioni luminose in molteplici contesti

Light output 1




1 x Halogen low voltage lamp without reflector

Nominal lamp power	35 W	Socket	Gu5.3
Lamp flux	600 lm	LOR	100%
Luminous efficacy	17 lm/W	Total flux	600 lm
CCT	3000 K	Total power	35 W
CRI	100		




1 x Halogen low voltage lamp without reflector

Nominal lamp power	35 W	Socket	Gu5.3
Lamp flux	630 lm	LOR	100%
Luminous efficacy	18 lm/W	Total flux	630 lm
CCT	3000 K	Total power	35 W
CRI	100		




1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gu5.3
Lamp flux	865 lm	LOR	100%
Luminous efficacy	17 lm/W	Total flux	865 lm
CCT	3000 K	Total power	50 W
CRI	100		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gu5.3
Lamp flux	1025 lm	LOR	100%
Luminous efficacy	20 lm/W	Total flux	1025 lm
CCT	3000 K	Total power	50 W
CRI	100		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gu5.3
Lamp flux	925 lm	LOR	100%
Luminous efficacy	18 lm/W	Total flux	925 lm
CCT	3000 K	Total power	50 W
CRI	100		

Mounting mode

Wall mounted

Shape and measurements

Length: 4.19 in

Width: 2.76 in

Height: 18.31 in

Adjustability

Fixed

Electric

System power: 35-50 W

Protection

IP: 20