


Product data sheet

IYON S LED1900-930 LDO 3CY FL-S BKMM
60715091
ZUMTOBEL



LED spotlight with stabilised colour temperature "Essential+ stableWhite"; optimised for efficient accent lighting in shops and showrooms; sparkling accentuation thanks to precision reflector; compact, timeless spotlight design, specially developed for integrating high-power LED modules; innovative thermal design achieves passive cooling; Luminaire with L3+DALI universal adapter for DALI controller with control gear unit in trackbox adapter (for Zumtobel 3-phase/L3+DALI track), only connection with LDE or LDO, Slave luminaire for DALI control (DALI only); lamp(s): 1/24W LED1900-930; Colour rendering Ra > 90, colour temperature 3000 K (warm white); Luminaire or spotlight with FLOOD light distribution, with rotationally symmetrical reflector in silver colour; Chromaticity tolerance (initial MacAdam): 3; Luminaire luminous flux: 1900 lm, Luminaire efficacy: 79 lm/W; service life: 50000 h for luminous flux at 80% of initial value; UVA-free and IR-free light; total power: 24 W; mains voltage: 220-240V/ 50/60Hz; spotlight can rotate through 360° and tilt through 90°; spotlight housing made of die-cast aluminium, surface finish: microtextured paint in black, matt; front ring fixed to spotlight housing by twist-and-lock mechanism; easy tool-free replacement of reflector and accessories; specular reflector made of aluminium-sputtered polycarbonate with mirrorbrite, iridescent-free finish; specular reflector designed for easy replacement and conversion; dimensions: 160 x 100 x 261 mm; weight: 0.8 kg; Please note: adapter version suitable for mounting on wall; not suitable for point outlets.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	24 W	CRI	90
Total flux	1900 lm	LOR	100%
Luminous efficacy	79 lm/W	Total power	24 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 6.30 in

Width: 3.94 in

Height: 10.28 in

Weight: 0.8 kg

Design

Material impression: Aluminum

Color of housing: Black

Electric

System power: 24 W

Voltage: 220-240 V AC

Controller: DALI

Appliance Class: I

Protection

IP: 20

Designation labels: CE