

Product data sheet

PTECDHO L60 60 & PTECD SSR * DGR


PROTEC LED HO

DEXTRA



Protec LED High Output - Ø174mm, IP20 Recessed High Output Downlighter with a 60 Degree Lens, ABS housing and bezel, zinc plated spring steel fixing clips and anodised semi specular aluminium reflector and drop glass ring. E3 - Emergency control gear (416 lumens output) - Attachments may reduce emergency lumen output. ST3 - Emergency Selftest AT3 - Emergency Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)* Replace * with WH for White or GY for Grey Order the luminaire with trim accessory attachment

Light output 1 (integrated)



| | | | |
|--------------------|----------|-------------|--------|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 36.9 W | CRI | 80 |
| Total flux | 4927 lm | LOR | 100% |
| Luminous efficacy | 134 lm/W | Total power | 36.9 W |

Mounting mode

Ceiling recessed

Shape and measurements

Height: 5.12 in

Diameter: 6.89 in

Adjustability

Fixed

Electric

System power: 36.9 W

Ballast: ECG

Protection

IP: 20

Designation labels: CE