


Product data sheet

SRN L63 PC
SIREN
DEXTRA



Siren - 1500mm, IP65, IK07 Surface mounted moisture resistant luminaire. Polycarbonate body and diffuser with stainless steel diffuser retaining clips. Options: S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) H - HFR Analogue 1-10v C - Bi-Level Dimming (Corridor Function) RLI - Reacta-Link, Wireless Enabled Luminaire RC - Reacta-Control, Wireless Enabled Luminaire LE3 - Lithium Standard Emergency 3 Hour LS3 - Lithium Selftest Emergency 3 Hour LA3 - Lithium Autotest Emergency 3 Hour TRS - Tamper Resistant Screws TRS INSTALL KIT - Tamper Resistant Compatible Screwdriver Heads

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	39.3 W	CRI	80
Total flux	5294 lm	LOR	100%
Luminous efficacy	135 lm/W	ULOR	8%
		Total power	39.3 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 59.06 in

Width: 3.94 in

Height: 2.95 in

Adjustability

Fixed

Electric

System power: 39.3 W

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Protection

IP: 65

IK: 07

Designation labels: CE