


Product data sheet

SL720+ SM RL 24 S/B 830 WH9016 BT MP
3114882
PERFORMANCE IN LIGHTING



LED surface-mount luminaire for indoor, comprising: Extruded aluminium housing profile, powder-coated. Fitted frame made of sheet steel, powder-coated. Micro-prismatic diffuser for efficient light distribution, glare reduction and high uniformity (MP). VDU application suitable acc. to EN 12464-1. LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover. Easy, subsequent replacement of the LED modules in just a few simple steps (can also be carried out without an electrician). Predominantly direct light distribution. Colour rendering index Ra > 80. Colour tolerance according to MacAdam ≤ 3 SDCM. Dimmable via TouchDIM®. With the "OSRAM BT Control" Bluetooth control, the light can be easily configured, personalised or grouped via the app using various parameters. In the tunable white version, the illuminance level and light colour can be manually adjusted from 2700K to 6500K depending on the time of day (DALI DT8). In the HCL version, the illuminance level and light colour can be manually adjusted from 2700K to 6500K depending on the time of day (DALI DT8). Special colour versions available. Consult factory

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	26 W	CRI	80
Total flux	3195 lm	LOR	100%
Luminous efficacy	123 lm/W	ULOR	5%
		Total power	26 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 49.69 in
Width: 10.43 in
Height: 0.71 in

Design

Color of housing: White

Electric

System power: 26 W
Appliance Class: I

Protection

IP: 20