



# Product data sheet

MINICONFINE 1200 1 X 9W 78° X 47° 4000 K  
GH1182.ENAT400EN  
GHIDINI



Series of linear luminaires to be recessed in-ground with reduced recess depth and various sizes and dimensions. Designed for the lighting of facades, walls with a "wall wash" effect thanks to the wide availability of optics and powers. The outer frame in stainless steel makes it resistant to trampling and gives it a refined look. The body and the side plugs are constructed of high oxidation resistant aluminum alloy which is subjected to nano-bonderite treatment and finished with texturized polyester powder paint, making the product resistant to atmospheric agents and UV rays, guaranteeing maximum protection over the years. Silicone gaskets ensure maximum sealing in all operating and temperature conditions. The ultra transparent tempered sodium calcium glass diffuser ensures maximum light transmittance and is finished with a silkscreen border. The product is equipped with the Ghidini water-lock system which prevents condensation from the power cable due to the alternating on and off cycles. The product is installed with a polypropylene rough-in housing that prevents the contact of the fixture directly with the ground and allows the necessary space for wiring. The product can be walked on and installed in areas not permitted for traffic. Not suitable for installation in swimming pools or fountains.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	36 W	CRI	90
Total flux	2811 lm	LOR	100%
Luminous efficacy	78 lm/W	Total power	36 W

## Mounting mode

Floor recessed

## Shape and measurements

Length: 48.43 in

Width: 2.95 in

Height: 0.12 in

## Adjustability

Fixed

## Electric

System power: 36 W

Appliance Class: I

## Protection

IP: 68