

Product data sheet

LED PERFORMANCE DAMPPROOF 1200 15W865 G3
4058075586918
LEDVANCE




IP
65

IK
08

Available in six wattages and lumen packages. Available in 3 length options, ensuring direct replacement of traditional 2/4/5 feet fluorescent dampproof fixtures. High system lumen efficacy: 130lm/W. High color rendering: CRI >80. Standard 4000K & 6500K CCT. Anti corrosion stainless steel clips. IP65, IK08. Safety compliance certificates: CB. DALI version and self contained emergency versions are available within the same family. UV stabilized polycarbonate opal diffuser for uniform light distribution and long durability. Polycarbonate body and diffuser offers IK08 impact protection. Sleek and lightweight slim body design, compact but powerful. Long 50,000hr lifetime reduces maintenance costs.

Light output 1 (integrated)



Lamp type	LED	CCT	6800 K
Nominal lamp power	15 W	CRI	80
Total flux	2000 lm	LOR	100%
Luminous efficacy	133 lm/W	ULOR	7%
		Total power	15 W

Mounting mode

Ceiling mounted

Electric

System power: 15 W

Shape and measurements

Length: 47.24 in

Width: 2.56 in

Height: 1.18 in

Protection

IP: 65

IK: 08

Adjustability

Fixed