Product data sheet


ARKA-E1497DAWS840AS0600
0833037
RIDI



IP 20

Einbauleuchte Ausführung: Deckenleuchte aus Stahlblech mit mikroprismatischem Diffusor. Lichtlenkung durch Abdeckung satiniert, Ausstrahlungscharakteristik asymmetrisch, extrem breitstrahlend, Lichtaustritt direkt. LED-Modul linear, Farborttoleranz (SDCM) < 3 SDCM, Leuchtmittel Austausch durch Fachkraft. Lichtstrom einstellbar stufenlos. Deckenleuchte rechteckig, aus lackiertem Stahl in verkehrsweiß, ähnlich RAL 9016, bzw. silber, ähnlich RAL 9006, lichtbandfähig, Schutzart IP20. Abdeckung aus PMMA klar. Einbaumontage als Einzel- oder Bandleuchte, Stirnteile separat zu bestellen. Bei Bandmontage ist der Leuchtenverbinder erforderlich. Pendelmontage mit separatem Zubehör, bei Bandmontage ein Abhänger pro Verbindungsstelle. Durchgangsverdrahtung als Zubehör verfügbar. Mit elektronischem Betriebsgerät. Austausch durch Fachkraft möglich. Nennspannung 220 - 240 V AC/DC 50 - 60 Hz, Schutzklasse I.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	37 W	CRI	80
Total flux	5760 lm	LOR	79%
Luminous efficacy	156 lm/W	ULOR	4%
		Total power	37 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 58.94 in
Width: 7.24 in
Height: 3.35 in

Adjustability

Fixed

Design

Color of housing: Silver gray, White

Electric

System power: 37 W
Appliance Class: I

Protection

IP: 20