
Product data sheet

LINEAR LIGHTING

V1-R0-1X827-02D01-4004027 X-LINE 2,00 M FOR CONTINUOUS LINES 40W 2700K


VARTON



IP 40 IK 01

• Extruded aluminum luminaire with flexible modular system for different shapes • L/T/X connectors • Continuous lines up to 30 m Application • Retail spaces • Administrative facilities Installation • Surface-mounted • Suspended (optional) Input voltage (AC, 50Hz), V: 176...264 AC frequency, Hz: 50 Flicker, %: 1 Climatic modification and category of placement: УХЛ4 Color rendering index: 80-89 Protection class: I Mounting method: Pendant Ingress protection (IP): IP40 Radiation angle: Radiation angle, °: 100 Impact resistance: IK01 Power factor: 0,95 https://www.varton.ru/products/lineynye-svetilniki-dlya-vnutrennego-osveshcheniya/x-line-dlya-sborki-v-liniyu/x-line-2-00-m-dlya-sborki-v-liniyu/svetodiodnyy-svetilnik-varton-x-line-dlya-sborki-v-liniyu-40-vt-2700-k-1990x63x100-mm-ral9003-belyy-_2/

Light output 1



1 x LED

Nominal lamp power	40 W	LOR	100%
Lamp flux	4100 lm	Total flux	4101 lm
Luminous efficacy	102 lm/W	Total power	40 W
CCT	2700 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 78.35 in
Width: 2.48 in
Height: 3.94 in

Adjustability

Fixed

Electric

System power: 40 W

Protection

IP: 40
IK: 01