


Product data sheet

LINEDO_1,2M_00_00
951200.002.500.900
RZB




IP
54

IK
03

Series: LINEDO Rapid-installation complete module for universal use as a continuous line luminaire. Blank module. System profile made of aluminium extrusion profile, powder-coated. Cover made of plastic, surface like housing. Simple, tool-free installation of system profiles using separate accessories for cable, chain or ceiling suspension. Tool-free connection and mechanical connectors to secure. Please order supply module, connection and mounting accessories separately. Luminaire with limited surface temperature in accordance with EN 60598-2-24 for use in environments where non-conductive dust deposits on the luminaire can be expected. Colour: traffic white, matt (RAL 9016) Length: 1163 mm Width: 58 mm Height: 76 mm Weight: 2,09 kgType of Installation: Ceiling mounting, Suspension cable/chain

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	0.01 W	CRI	80
Total flux	1 lm	LOR	100%
Luminous efficacy	100 lm/W	Total power	0.01 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 2.28 in
Width: 45.79 in
Height: 2.99 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 0.01 W

Protection

IP: 54
IK: 03