




Product data sheet

SMART [4] 1M HLO 840 60° DALI EMERGENCY
GWS4124BH840
GEWISS




Smart [4] is the range of lighting fixtures developed and produced in Italy with latest generation LEDs and new optics solutions (reflector optics and PMMA lenses), that warranties excellent lighting performance and always more energy efficiency. A wide and flexible range, available in three sizes (1 module, 2 modules and 4 modules), luminous fluxes up to 36,400 lm and different colour temperature options (3000K, 4000K, 5700K). The new design (grey RAL 7035) adapts perfectly to medium and large contexts (such as industries or indoor sports areas), both with Stand Alone application and through wiring, thanks to the special accessories that allow a wide flexibility during installation also.

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	1 W	CRI	80
Total flux	949 lm	LOR	100%
Luminous efficacy	949 lm/W	Total power	1 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	69 W	CRI	80
Total flux	9900 lm	LOR	100%
Luminous efficacy	143 lm/W	Total power	69 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 25.04 in

Width: 9.96 in

Height: 4.80 in

Adjustability

Fixed

Electric

System power: 70 W

Ballast: ECG

Controller: DALI

Appliance Class: II

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Design

Material impression: Plastic

Color of housing: Anthracite / graphite, Silver gray

Designer: Gewiss

Protection

IP: 65

IK: 08

Designation labels: CE

Other operating numbers

Ambient temperature range: 32...104°F