


# Product data sheet

RIGMASTER™ LED LINEAR 7650 LUMEN 3000 K CCT-DIFFUSED PC- 180 MIN EMERGENCY  
I/RMA42WDLBUE  
APPLETON (EMERSON EGS)




Rigmaster LED Linear Series 180 min Emergency 3/4" NPT Hub NEMA Type V Symmetrical 3000 K CCT/ 80 CRI Voltage- BU-120-277V, 50/60Hz BH-347-480 Vac, 50/60Hz Class I, Division 2, Groups A, B, C, D Class I, Zone 2, Group IIC Glass II, Division 2, Group F, G Class II, Zone 22, Class III Type 3R,4, 4X IP66 Suitable for Use in Wet Locations Refer to catalog for additional options

## Light output 1 (integrated, emergency)



Lamp type	LED	CCT	3114 K
Nominal lamp power	6.49 W	CRI	80
Total flux	586 lm	LOR	100%
Luminous efficacy	90 lm/W	Total power	6.49 W

## Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	55.32 W	CRI	80
Total flux	5162 lm	LOR	100%
Luminous efficacy	93 lm/W	Total power	55.32 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 1.77 in  
Width: 41.34 in  
Height: 4.17 in

## Adjustability

Fixed

## Electric

System power: 61.81 W  
Appliance Class: II

## Information regarding emergency functions

Supplementary emergency lighting  
Emergency sign: N/A

## Protection

IP: 66  
Explosion zone suitability: 2, 22