


# Product data sheet

3384 COMO 2 - ASYMMETRIC 4000K CRI 70 9W CLD ANTHRACITE  
340560-00  
DISANO



Housing: die-cast aluminium, designed with a very small surface exposed to wind. Attachment: suited for poles with a diameter between 60 and 76 mm. Optics: in high-performance PMMA resistant to high temperatures and UV rays. Diffuser: tempered glass, 4 mm thick, resistant to thermal shock and impact (UNI EN 12150-1:2001). Coating: pre-treatment of metal surface, polyester powder coating to ensure resistance to corrosion and salt spray fogs, UV stabilised. Special coating: upon request: available with coating tested to withstand corrosion tests in aggressive artificial atmospheres (UNI EN ISO 9227) or marine environments (sea front). Heat Sink: the heat sink is designed and made to allow the LEDs to operate at temperatures capable of ensuring excellent performance/output and long service life. Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529. Equipment: - IP67 quick connector. - anti-condensation valve. - temperature controller with auto-reset. - EN 61547 compliant surge protection. - BASIC PROG built-in functions.

## Light output 1



1 x LED			
Nominal lamp power	9 W	LOR	100%
Lamp flux	1420 lm	Total flux	1420 lm
Luminous efficacy	158 lm/W	Total power	9 W
CCT	4000 K		
CRI	70		

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 15.75 in  
Width: 15.75 in  
Height: 24.53 in

## Adjustability

Fixed

## Design

Material impression: Aluminum  
Color of housing: Anthracite / graphite

## Electric

System power: 9 W  
Appliance Class: II

## Protection

IP: 66  
IK: 09  
Designation labels: CE, ENEC

## Other operating numbers

Ambient temperature range: -22...104°F