


# Product data sheet

PETRA  
9.895.5562.40  
LEIPZIGER LEUCHTEN



Mounting height 3.30 / 4.00 m. - Impact-resistant opal polycarbonate cylinder, UV-stabilized - Two large aluminium reflectors with a special white paint finish provide max. light reflection - Available in any RAL or DB color without surcharge - All electrical components on a block which is accommodated in the crown of the luminaire - Lamps are easy to change - A pole, dia. 102 mm throughout, and a frame made of hot galvanized and painted steel or special steel, ground and passivated are included in the scope of supplies delivery Hauteur de feu: 3.30 et 4.00 m Voltage: 230V 50Hz Protected to: IP 65 Protection class: I/II Made to DIN VDE 0711

## Light output 1



2 x DULUX L-SP			
Nominal lamp power	24 W	LOR	100%
Lamp flux	1800 lm	Total flux	3600 lm
Luminous efficacy	67 lm/W	Total power	54 W
CCT	2899 K		
CRI	90		

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 16.14 in  
Diameter: 3.94 in

## Electric

System power: 54 W

## Integrated sensors

Integrated sensors: Daylight sensor, Motion sensor

## Protection

IP: 65  
Designation labels: CE