Product data sheet

ECLDISPLAY_BLACK
ECLDISPLAYCCVW_CW_PROFILE1020_MAX ZOOM
PROLIGHTS



IP 20 IK 08

The EclDisplay is a range of revolutionary and flexible LED spotlights designed for galleries, retail and any public venue where an advanced but classical looking fixture is needed, with several control options, sources and optic versions available to precisely meet any application. The EclDisplay CCVW is the version of the EclDisplay range made to be connected to an external Constant Current PSU and driver (max 700mA/36V), selecting among the PROLIGHTS accessories or any third-party compatible component, leaving to System Integrators to install this luminaire in venues with their own wiring distribution and control. The EclDisplay CCVW includes a high-efficiency 35W tunable white, high CRI LED source, with a CCT range from 2,700K to 5,600K, and it is completed with a wide selection of optional zoomable profile or wash lenses, and other optical accessories like louvres and snoots, making it truly a multi-purpose fixture. Features: Constant Current version to be connected to external PSU and driver (max 700mA/36V) 35W high CRI tunable white LED, from 2,700K to 5,600K, in black and white housing Multiple lens options: zoomable profile or wash optics

Light output 1



1 x LED

Nominal lamp power	31.9 W	LOR	100%
Lamp flux	1282 lm	Total flux	1285 lm
Luminous efficacy	40 lm/W	Total power	31.9 W
CCT	6237 K		
CRI	96		

Mounting mode

Ceiling mounted, Contact rail, Standing / Bollard

Shape and measurements

Length: 39.37 in
Width: 39.37 in
Height: 39.37 in

Adjustability

Rotatable, Tiltable, Free

Electric

System power: 31.9 W
Controller: DMX, DALI
Color adjustable
Appliance Class: I

Protection

IP: 20
IK: 08
Surface temperature: 65°C
Designation labels: CE