

# Product data sheet

GLASSGLASS


D31 P/9

LUCEPLAN




La versatilità di un sistema componibile e l'eleganza del pezzo unico. La struttura a maniglia in alluminio pressofuso sostiene con sicurezza una serie di vetri diffusori realizzati secondo le antiche tradizioni della soffiatura. Il cavo elettrico, ingabbiato in una maglia di acciaio, è portante.

## Light output 1




### 1 x Halogen low voltage lamp without reflector

|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 205 W   | Socket      | E27     |
| Lamp flux          | 2520 lm | LOR         | 84%     |
| Luminous efficacy  | 9 lm/W  | ULOR        | 47%     |
| CCT                | 2821 K  | Total flux  | 2125 lm |
| CRI                | 99      | Total power | 250 W   |



### 1 x Halogen low voltage lamp without reflector

|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 140 W   | Socket      | E27     |
| Lamp flux          | 2840 lm | LOR         | 84%     |
| Luminous efficacy  | 10 lm/W | ULOR        | 47%     |
| CCT                | 3000 K  | Total flux  | 2395 lm |
| CRI                | 99      | Total power | 250 W   |



### 1 x Halogen low voltage lamp without reflector

|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 105 W   | Socket      | E27     |
| Lamp flux          | 1980 lm | LOR         | 84%     |
| Luminous efficacy  | 7 lm/W  | ULOR        | 47%     |
| CCT                | 3000 K  | Total flux  | 1670 lm |
| CRI                | 99      | Total power | 250 W   |

## Mounting mode

Pendant

## Electric

System power: 250 W

#### Shape and measurements

Length: 9.12 in

Width: 8.96 in

Height: 22.12 in

#### Adjustability

Fixed

#### Protection

IP: 20