Product data sheet


STELLA L V/07 DA LED (OPTIC 268)
9.628.8110.677268-3ALA
LEIPZIGER LEUCHTEN



IP 65

• luminaire head with cap made of aluminium; powder coated; straight tubular column made of aluminium with access door for cable junction box; powder coated • wall bracket with wall shield made of hot-dip galvanised steel; powder coated • glazing made of PMMA RESIST, clear, high-impact resistant • STELLA L: completely wired; incl. cable until access door; WL STELLA: via a plug and socket connector below the luminaire heads • with flange plate to be screwed on a concrete foundation on site or on an additional bolt-on root or with root to be set into the ground; wall luminaire: to be screwed to the wall • to be ordered separately: column accessories, cable junction box, bolt-on root (G240/800) with screws, accessory ring (Z248/1), cable and fixing material for the wall installation, bird defl ector, back light shield for no glare on the rear side

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	9 W	CRI	70
Total flux	1108 lm	LOR	84%
Luminous efficacy	123 lm/W	Total power	9 W

Mounting mode

Standing / Bollard

Shape and measurements

Height: 145.67 in
Diameter: 6.69 in
Weight: 34.5 kg

Adjustability

Fixed

Electric

System power: 9 W

Protection

IP: 65