Product data sheet

UPLIGHT STREAM OFFICE HIGH 143W CRI > 80 3000K BLACK 2.5M POWER SUPPLY CABLE WITH 2001.8398 - STREAM HIGH1800 LED16000-830 WB BK REG CH


REGENT



IP 20

Uplight Stream Office High, system power: 143 W, with LED, luminous flux of luminaire 16000 lm, standby power 0.3 W, colour rendering index CRI > 80, 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, office-compatible and glare-free according to EN 12464-1 (UGR < 19; Lmax ≥ 65° ≤ 3000 cd/m²), photobiological safety: the luminaire poses no danger (RG0), 230 V, indirect light emission, wide beam, with pushbutton on the housing, in aluminium, black, 1 integral control gear, dimmable digital, dimmable 10-100 %, 2.5m power supply cable with plug, standard-compliant and suitable for offices Regent certified MINERGIE®-Modul luminaires S.A.F.E. 2019 (Re-0317), luminaire complies with the strict requirements for Minergie-certified luminaires protection class I, ingress protection IP20, glow wire test 650 °C, this product contains a light source of energy efficiency class D and EPREL registration number: 988126 Ø = 141 mm, total height = 1800 mm, swivelling +/- 25°

Light output 1



1 x LED

Nominal lamp power	143 W	LOR	100%
Lamp flux	16000 lm	Total flux	15995 lm
Luminous efficacy	112 lm/W	Total power	143 W
CCT	3000 K		
CRI	80		

Mounting mode

Table luminaire

Shape and measurements

Length: 13.78 in
Width: 13.78 in
Height: 58.54 in
Weight: 24.97 kg

Adjustability

Free

Design

Color of housing: Black

Electric

System power: 143 W
Appliance Class: I

Protection

IP: 20