

Product data sheet


MINI BEAM
F05230/T5 FH 2X35W/FQ 2X49W
FLOS




IP
20

Suspension luminaire with direct/indirect lighting. Directly modular connection without joint. Liquid-painted aluminium body. Chrome-plated plastic end caps. Galvanized steel structural parts.

Light output 1



| | | | |
|---------------------------------|---------|-------------|---------|
| 2 x Fluorescent lamp tubular T2 | | | |
| Nominal lamp power | 49 W | Socket | G5 |
| Lamp flux | 4300 lm | LOR | 91% |
| Luminous efficacy | 80 lm/W | ULOR | 34% |
| CCT | 2700 K | Total flux | 7843 lm |
| CRI | 82 | Total power | 98 W |



| | | | |
|---------------------------------|---------|-------------|---------|
| 2 x Fluorescent lamp tubular T2 | | | |
| Nominal lamp power | 35 W | Socket | G5 |
| Lamp flux | 3300 lm | LOR | 91% |
| Luminous efficacy | 86 lm/W | ULOR | 34% |
| CCT | 2700 K | Total flux | 6019 lm |
| CRI | 82 | Total power | 70 W |

Mounting mode

Pendant

Shape and measurements

Length: 60.00 in
Width: 7.87 in
Height: 1.34 in

Adjustability

Fixed

Electric

System power: 70-98 W

Protection

IP: 20