


Product data sheet

AGAR BOLLARD
7123-0-3-905-XX
UNILAMP



AGAR a range of wall light and bollard with high power LED and AC COB light sources. It is generally installed in the walk ways, parks and open spaces. It provides general lighting for the architectural environment as well as being an eye-catching object. The diffuser lens in prismatic or opal are made from polycarbonate for vandal resistance. The lens spreads the light evenly on walls and any surfaces. We can produce the bollard at different height accordingly for customized solutions. An anchorage unit for is available as an accessory. Spec • Designed, Manufactured and tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium and Extruded Aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Polycarbonate diffuser. • Post-cured silicone gasket. • High quality LED module and driver. • GFR PA6.6 Terminal block. • Weather proof TPE grommet. • Bollard pre-wired with outdoor cable. • Installation work has to be carried on according to the enclosed product manual.

Light output 1



1 x LED			
Nominal lamp power	36 W	LOR	100%
Lamp flux	4920 lm	ULOR	7%
Luminous efficacy	137 lm/W	Total flux	4920 lm
CCT	4000 K	Total power	40 W
CRI	80		

Mounting mode

Standing / Bollard

Shape and measurements

Length: 12.56 in

Width: 12.76 in

Height: 35.24 in

Adjustability

Fixed

Electric

System power: 40 W

Appliance Class: II

Protection

IP: 65

IK: 08