



Product data sheet

2897 3000K CRI 80 100W CLD BLACK + SETTING CONFIG
380093-00+60G
DISANO



Housing: in die-cast aluminium with cooling fins integrated in the cover. Optics: polycarbonate with concentric rings. Coating: the fully automated powder-coating cycle involves a polyester-based, salt-spray corrosion-resistant and UV-stabilised paint. Heat Sink: the heat sink is designed and made to allow the LEDs to operate at temperatures capable of ensuring excellent performance/output and long service life. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. They have a degree of protection according to the EN60529 standard. Equipment: the fixture is equipped with waterproof connector for quick installation; external screws and bolts in stainless steel., version equipped with eyebolt for suspension installation.

Light output 1



1 x LED			
Nominal lamp power	100 W	LOR	100%
Lamp flux	15760 lm	Total flux	15759 lm
Luminous efficacy	158 lm/W	Total power	100 W
CCT	3000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Height: 6.89 in
Diameter: 12.20 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 100 W
Appliance Class: I

Protection

IP: 65
IK: 08
Designation labels: CE

Other operating numbers

Ambient temperature range: -40...104°F