Product data sheet

NADJA III (WALL FITTING BEADED) 9.846.2036.06

LEIPZIGER LEUCHTEN








Recommended mounting height 3.50 - 5.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1




I x High pressure sodium vapo	ur lamp
Nominal lamp power	50 W
Lamp flux	3500 lm

Luminous efficacy 44 lm/W CCT 2000 K CRI

LOR 78% Total flux 2729 lm Total power 62 W

25



1 x High pressure sodium vapour lamp

CRI

Nominal lamp power 70 W LOR 78% Lamp flux 5600 lm Total flux 4366 lm Luminous efficacy 53 lm/W Total power 83 W CCT 2000 K

Mounting mode

Wall mounted

Shape and measurements

Height: 16.54 in

Diameter: 16.54 in

Electric

System power: 62-83 W

25

Protection

IP: 55

Designation labels: CE, ENEC, F