Product data sheet

INFINITE PRO 854MM SURFACE OPTICELL
AK11-24W8CLWR60
LEDSC4



IP 40

LedsC4 Infinite Pro 854mm Surface Opticell AK11-24W8CLWR60 Lineal lighting system for indoor use. For downlighting. Structure finish: Black. Diffuser material: Polycarbonate. Diffuser finish: Opticell. Warranty: 5 Years. Product net weight (Kg): 1.95 Product length (mm): 854 Product width or diameter (mm): 52 Product height (mm): 90 Class 1. IP: IP40. LED. No. of lampholders or LEDs: 1. LED brand: TRIDONIC. Driver brand: PHILIPS. Maximum power of light source: 22W. Colour temperature: 3000K. Colour rendering index: 80. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 17.9. Photobiological risk: RG1. % de Flickering: <4%. Real flux (lm): 3685. Real lm/W: 151. Voltage / frequency range: 220-240/50-60Hz. Voltage: 120. Equipment included: Yes. Total power: 24.4. Power factor: 0.90. Dimmable equipment included: DALI D4i.

Light output 1



1 x LED

Nominal lamp power	24.47 W	LOR	100%
Lamp flux	3685 lm	Total flux	3684 lm
Luminous efficacy	151 lm/W	Total power	24.47 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted, Standing / Bollard

Shape and measurements

Length: 2.05 in
Width: 33.46 in
Height: 3.54 in

Adjustability

Fixed

Electric

System power: 24.47 W
Appliance Class: I

Protection

IP: 40