


Product data sheet

RAMATUELLE 648
EVO2 RAMATUELLE-648-PC02 45D-24LED-4000K-700 MA
RAGNI



The LED module is specially designed to replace traditional asymmetrical road reflectors. It is composed of a die-cast aluminium heat sink, a tempered glass cover and a cellular silicone gasket. The module is available in a sealed version (IP 66) with pressure regulating vent. Its impact resistance index is IK 08. Electrical class II, it receives from 8 to 64 LEDs @ 700 mA, and offers multiple color temperatures and light distributions. The module can be coupled to a management system to adapt lighting to needs and save energy. Equipped with a passive finned heatsink located behind the PCB, it is in contact with the luminaire body to improve thermal conduction. It is also equipped with a cable gland. Driver and PCB to Zhaga standards (Zhaga book 13, 15), the module is compatible with almost all of our luminaires. Its ULR is 0% and it is EEC eligible (case n°1), in accordance with the requirements of the NF EN 13201 standard and RoHs requirements.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	52.1 W	CRI	70
Total flux	6902 lm	LOR	100%
Luminous efficacy	132 lm/W	Total power	52.1 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 19.69 in

Width: 19.69 in

Height: 19.69 in

Adjustability

Fixed

Electric

System power: 52.1 W

Appliance Class: II

Protection

IP: 66

IK: 08