Product data sheet


LTUB60 SU RE 1680 3000 WW OPAL WH
L61SE168MOOP930NW
LAMP



IP 20 IK 07

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 1680mm, with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 3000K with CRI 90. Built-in electronic ON/OFF control gear. With IP20, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

Light output 1



1 x LED

Nominal lamp power	34.7 W	LOR	100%
Lamp flux	3089 lm	Total flux	3088 lm
Luminous efficacy	89 lm/W	Total power	34.7 W
CCT	3000 K		
CRI	90		

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Length: 68.03 in
Width: 2.76 in
Height: 2.56 in

Adjustability

Fixed

Design

Color of housing: Black, White

Electric

System power: 34.7 W
Appliance Class: I

Protection

IP: 20
IK: 07